


STANDARD DEPARTURE CHART
INSTRUMENT (SID) - ICAO

TRANSITION ALTITUDE
6000

Alt set: - hPa (mm on req)
-QNH (QFE on req)

DIST IN NM
BEARINGS ARE MAGNETIC
ALTITUDES AND ELEV IN FT
VAR 9° E 2019

RNAV 1
GNSS, DME/DME or DME/DME/IRU



MINSK APP	125.900
MINSK RADAR	125.250
MINSK TOWER RWY 13R/31L	118.300
MINSK TOWER RWY 13L/31R	130.400
MINSK-2 ATIS	128.850 EN 135.850 RUS

MINSK-2
RNAV RWY13R

AGNEF2A, ARZIM2A
KUBIN2A, OSMUS2A
SORFO2A, TAZIP2A

RNAV 1 APPROVAL REQUIRED. OTHERWISE ADVISE ATC.

EXPECT DIRECT ROUTING/SHORTCUTS BY ATC WHENEVER
POSSIBLE (ESPECIALLY DURING OFF-PEAK HOURS, SEE GEN 4.1
POINT 8).

INITIAL CLIMB

CLIMB AND MAINTAIN 6000 FT.
CLIMB TO A HIGHER LEVEL ONLY WHEN CLEARED BY ATC.

THE MINIMUM CLIMB GRADIENTS ARE AS FOLLOWS

(REQUIRED FOR SEPARATION REASONS):

- 5.7% FOR SID OSMUS 2A UP TO FL 170
- 6.0% FOR SID AGNEF2A, SORFO 2A, UP TO FL 130
- 6.0% FOR SID KUBIN 2A UP TO FL 170

WARNING

IF UNABLE TO COMPLY PDG REPORT AT FIRST CONTACT WITH
MINSK GND.

RADIO COMMUNICATION FAILURE PROCEDURE

SET TRANSPONDER TO 7600.

IF AVAILABLE CALL TELEPHONE NUMBER +375172157600.

ATTEMPT TO LAND AT THE AERODROME OF DEPARTURE.

IF UNABLE TO LAND AT THE AERODROME OF DEPARTURE:

CONTINUE ASSIGNED AND ACKNOWLEDGED SID;

AFTER REACHING THE LAST ASSIGNED FLIGHT LEVEL, CONTINUE
FURTHER CLIMB TO FPL FLIGHT LEVEL IN 3 MINUTES.


IF BEING VECTORED

SET TRANSPONDER TO 7600.

CONTINUE ON ASSIGNED HEADING AND FLIGHT LEVEL FOR 3
MINUTES, THEN PROCEED DIRECT TO FINAL SID POINT,
CLIMBING TO FPL FLIGHT LEVEL.

UMR258 & UMR 269 ARE NOT APPLICABLE FOR
AIRCRAFTS PERFORM TAKE OFF AND
LANDING AT AERODROME MINSK-2

SCALE 1:750,000



CHANGE: New chart.

TABULAR DESCRIPTION

AGNEF2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS111	-	066(075.0)	9	15.6	-	-FL100	-	RNAV1
004	TF	MS112	-	360(009.2)	9	10.5	-	+FL130	-250	RNAV1
005	TF	MS113	-	360(009.2)	9	5.8	-	-	-	RNAV1
006	TF	MS114	-	360(009.3)	9	9.0	-	-	-	RNAV1
007	TF	AGNEF	-	360(009.3)	9	14.3	-	-	-	RNAV1
ARZIM2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS151	-	130(139.0)	9	9.3	-	-	-250	RNAV1
04	TF	MS121	-	130(139.2)	9	12.0	-	-	-	RNAV1
005	TF	MS122	-	091(100.3)	9	11.5	-	-FL150	-	RNAV1
006	TF	ARZIM	-	092(100.5)	9	9.6	-	-	-	RNAV1
KUBIN2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS111	-	066(075.0)	9	15.6	-	-FL100	-	RNAV1
004	TF	MS112	-	360(009.2)	9	10.5	-	+FL130	-250	RNAV1
005	TF	MS113	-	360(009.2)	9	5.8	-	-	-	RNAV1
006	TF	MS114	-	360(009.3)	9	9.0	-	+FL170	-	RNAV1
007	TF	KUBIN	-	289(298.5)	9	41.9	-	-	-	RNAV1
OSMUS2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS102	-	220(228.7)	9	5.5	-	-	-	RNAV1
004	TF	MS103	-	276(285.0)	9	16.7	-	+FL110	-250	RNAV1
005	TF	MS104	-	273(282.2)	9	12.3	-	+FL150	-	RNAV1
006	TF	MS105	-	273(282.1)	9	5.5	-	+FL170	-	RNAV1
007	TF	OSMUS	-	273(281.7)	9	15.3	-	-	-	RNAV1
SORFO2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS111	-	066(075.0)	9	15.6	-	-FL100	-	RNAV1
004	TF	MS112	-	360(009.2)	9	10.5	-	+FL130	-250	RNAV1
005	TF	MS113	-	360(009.2)	9	5.8	-	-	-	RNAV1
006	TF	SORFO	-	035(043.9)	9	16.1	-	-	-	RNAV1
TAZIP2A										
Serial Number	Path Descriptor	Waypoint Identifier	Fly - over	Course °M(°T)	Magnetic Variation(°)	Distance NM	Turn Direction	Altitude FT	Speed KT	Navigation Specification
001	CF	MS100	Y	130(138.8)	9	3.1	-	-	-210	RNAV1
002	TF	MS101	-	130(138.9)	9	4.9	-	-	-	RNAV1
003	TF	MS151	-	130(139.0)	9	9.3	-	-	-250	RNAV1
004	TF	TAZIP	-	186(195.0)	9	33.5	-	-	-	RNAV1

STANDARD DEPARTURE CHART

INSTRUMENT (SID) – ICAO RNAV

WAYPOINT LIST		
Waypoint Identifier	Coordinates	
AGNEF	542909.0N	0284822.0E
ARZIM	532614.0N	0291013.0E
KUBIN	543517.0N	0274141.0E
MS100	534945.0N	0280635.2E
MS101	534602.2N	0281204.4E
MS102	534224.9N	0280506.4E
MS103	534646.4N	0273757.1E
MS104	534923.5N	0271740.5E
MS105	535032.7N	0270835.8E
MS111	535007.9N	0283732.2E
MS112	540029.0N	0284022.5E
MS113	540612.0N	0284157.2E
MS114	541504.2N	0284425.0E
MS121	532959.0N	0283532.2E
MS122	532757.4N	0285429.2E
MS151	533901.0N	0282223.0E
OSMUS	535341.0N	0264321.0E
SORFO	541749.0N	0290055.0E
TAZIP	530643.0N	0280749.0E

THIS PAGE INTENTIONALLY LEFT BLANK